

Side Mount Welding Hose Reels With Guide Arm

SGW Series

SGW Series expands the capabilities of the “Side Mount” spring driven hose reels, adding a multi-position guide arm for maximum and convenient hose control.

Ideal for tight spaces, the versatile SGW Series features a simple two-bolt mounting pattern for easy installation and detachment on any vertical flat surface including tool benches, service vehicles, tool boxes, vehicle lift systems, walls, beams, machine tools and more. The wide variety of applications allows Coxreels® to expand and offer this series for welding applications to store twin line of oxy-acetylene or “T” grade welding hose.

MODEL//SG17W-150



SGW SERIES Offers...

- External fluid path with 90° full-flow dual ported brass swivel offering both connections from the same side of the reel.
- Side mount design for vertical flat surface, cabinet or enclosed space mounts
- Adjustable 6 position guide arm & roller assembly provide maximum hose control
- Multi-position Locking Ratchet Secures Hose At Desired Length. Non-locking, Less Ratchet Option Available (Add Suffix –BXC)
- Controlled retraction speed up to 80% slower on EZ-Coil® models

Drive Type

Spring

Media

Oxy/Acete

Swivel material

Brass

Seal material

Viton

DUAL HOSE REEL // Oxyygen/ Acetelyne

MODEL hose	MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
SG17W-150	SG17WL-150	6 mm	12 mm	15 m	14	1/4"	1/4"	17	12	1
SG19W-175	SG19WL-175	6 mm	12 mm	23 m	14	1/4"	1/4"	24	16	2

DUAL HOSE REEL // Variety of fuel gasses

MODEL hose	MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG hose	KG no hose	Size
SG17WT-150	SG17WTL-150	6 mm	12 mm	15 m	14	1/4"	1/4"	17	12	1
SG19WT-175	SG19WTL-175	6 mm	12 mm	23 m	14	1/4"	1/4"	24	16	2



Also available in

EZ-COIL®

Please prefix the desired reel with “EZ-”

DIMENSIONS (in mm)

SIZE	A	B	C	D	E
1	226	495	432	64	457
2	267	559	495	74	520

