

Stainless Steel Hose Reels

SS Series

SS Series "Stainless Steel" hand crank and spring driven hose reels have similar features to their related series, but are constructed of high quality electro-polished stainless steel with stainless steel fluid paths. They offer clean, non-corrosive performance in applications that require it, such as food and chemical processing, marinas, and anywhere that rust, corrosion and contamination thrive.

SS SERIES Offers...

- High Quality Electro-Polished Stainless Steel Construction
- Non-Corrosive Stainless Steel Fluid Path Featuring Stainless Steel Swivel with Non-Toxic Grease



MOTOR

MANUAL

SPRING

Drive Type

Spring

Manual

Media

Air,

Water

Oil

Grease

Swivel material

S/Steel

Seal material

Viton

All models with suffix BGX come with a BSP inlet & outlet

P, SH & MP SERIES // Air, Water & Oil

MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG	Size
P-LPL-335-SS-BGX	10 mm	17 mm	11 m	21	3/8"	3/8"	15	1
P-LPL-350-SS-BGX	10 mm	17 mm	15 m	21	3/8"	3/8"	18	1
P-LPL-425-SS-BGX	12 mm	21 mm	8 m	21	1/2"	1/2"	18	2
SHL-N-350-SS-BGX	10 mm	17 mm	15 m	21	3/8"	3/8"	20	3
SHL-N-450-SS-BGX	12 mm	21 mm	15 m	21	1/2"	1/2"	21	3
SHL-N-525-SS-BGX	19 mm	29 mm	8 m	21	3/4"	3/4"	20	4
MPL-N-350-SS-BGX	10 mm	17 mm	15 m	210	3/8"	3/8"	24	3
MPL-N-450-SS-BGX	12 mm	21 mm	15 m	210	1/2"	1/2"	24	3

T SERIES // Air, Water & Oil

MODEL no hose	I.D.	O.D.	Length	BAR	Inlet	Outlet	KG	Size
TSHL-N-350-SS-BGX	10 mm	17 mm	15 m	21	3/8"	3/8"	25	5
TSHL-N-375-SS-BGX	10 mm	17 mm	23 m	21	3/8"	3/8"	33	6
TSHL-N-3100-SS-BGX	10 mm	17 mm	31 m	21	3/8"	3/8"	34	6
TSHL-N-450-SS-BGX	12 mm	21 mm	15 m	21	1/2"	1/2"	22	5
TSHL-N-475-SS-BGX	12 mm	21 mm	23 m	21	1/2"	1/2"	25	6
TSHL-N-4100-SS-BGX	12 mm	21 mm	30 m	21	1/2"	1/2"	36	6
TSHL-N-550-SS-BGX	19 mm	29 mm	15 m	21	3/4"	3/4"	32	7
TSHL-N-575-SS-BGX	19 mm	27 mm	23 m	21	3/4"	3/4"	34	7
TMPL-N-3100-SS-BGX	10 mm	27 mm	31 m	21	3/8"	3/8"	36	6
TMPL-N-4100-SS-BGX	12 mm	30 mm	31 m	21	1/2"	1/2"	37	6

EN SERIES // Air, Water & Oil

MODEL no hose	I.D.		Length	BAR	Inlet	Outlet	KG	Size
ENL-N-350-SS-BGX	10 mm	17 mm	15 m	21	3/8"	3/8"	26	8
ENL-N-450-SS-BGX	12 mm	21 mm	15 m	21	1/2"	1/2"	28	8

DIMENSIONS (in mm)

SIZE	A	B	C	D	E	F	G	L	M
1	172	474	435	153	153	-	-	102	127
2	178	474	435	153	153	-	-	102	127
3	210	540	496	153	153	-	-	102	127
4	239	540	496	153	153	-	-	102	127
5	239	540	496	204	229	-	-	178	204
6	239	648	610	204	229	-	-	178	204
7	251	648	610	204	229	-	-	178	204
8	216	553	556	153	153	-	-	102	127

